

# MODEL: X8 BODY WORN CAMERA



## INTRODUCTION

X8 records extremely clear and focused footage at distances ranging from a few centimetres to the horizon, requiring no user intervention. The camera is designed to operate in all reasonable lighting conditions, down to complete darkness, it also adapts rapidly to changing light levels, such as those when moving from daylight into a building.



### COMPACT AND LIGHTWEIGHT

X8 is very compact and weights only 140 gram, it does not weight down your movement in the field.



### 2K VIDEO RESOLUTION

Allows officer to capture 2K high quality video with improved low-light performance.



### WIDE ANGLE, LESS DISTORTION

130-degree camera lens provides for a greater field of view, allowing officer to capture more of what they experienced.



### H.265 CODEC

When it comes to storage, a high efficient video compression will be more preferable to save your resources.



### 12+ HOURS BATTERY LIFE

If a critical event happens, not having enough battery life left to capture the incident could be devastating, we provide 12+ hours battery life that supports your full shift.

## IP68

### IP68 RUGGED DESIGN

X8 is designed to withstand various extreme conditions, can be dropped and resistant against water or dust.

# MODEL: X8

# BODY WORN CAMERA

## SPECIFICATION

<b>Design</b>	Dimension	81mm×56mm×28mm
	Weight	140g
	Display	2.0-inch Screen
	LED Indicator	Yes
	AES-256 Encryption	Yes
	Type-C	Yes
<b>Video</b>	Video Resolution	2560×1440, 2304×1296, 1920×1080
	Encoding & Format	H.265 & H.264, MPEG-4
	Field of View	≥128°
	Distortion Correction	Auto
	Night Vision	Yes
	Tamper-Proof	User, S/N, Time & Date embedded on evidence
	Pre/Post Recording	Yes
<b>Battery</b>	Capacity	Built-in 3,200mAh Li-ion Polymer Battery
	Battery Life	12 hours
	Recharge Time	3 hours
<b>Storage</b>	Non-Removable	32GB
	Capacity	Store around 41 hours video at 720P, with H.265.
<b>Reliability</b>	Drop Test	2 Meters
	Dust/Water Protection	IP68
	Operating Environment	-30° C ~ 60° C
	Certificate	CE, RoHS, MIL-STD-810G, IEC 60529-2013